

A decorative graphic on the left side of the slide consists of a black crosshair. The vertical line is positioned to the left of a yellow square, a red square, and a blue square. The horizontal line extends from the crosshair across the slide.

TOLUENE REMEDIATION USING LOW VACUUM DUAL-PHASE EXTRACTION

Don Burnett, Chris Lach, and Alan Walker

Morrow Environmental Consultants Inc.

A decorative graphic consisting of overlapping yellow, red, and blue squares with a black crosshair.

Overview

- Background
- Remedial Objectives and Approach
- Additional Investigations
- System Design
- Operational Experience
- Progress to Date
- Questions

A decorative graphic consisting of overlapping yellow, red, and blue squares with a black crosshair.

Background


- Petrochemical plant operated 1961-1990
- Produced benzoic acid by catalytic oxidation of toluene
- Focus of talk is former Main Process Area (AES 1), approximately 11 acres
- COCs 520,000 kg aromatics:
 - 65% toluene, 20% benzene, 15% m-xylene





A decorative graphic consisting of overlapping yellow, red, and blue squares with a black crosshair.

Background

- Located on bank of major estuary
- 3 m to 3.6 m of uniform medium sand fill (2×10^{-4} m/s) over 1 m of overbank clayey silts over deltaic medium sand
- Recharge from 1.1 m rainfall October-May
- Shallow flow north to tidal river, south to slough and vertically downwards to deeper tidal aquifer





A decorative graphic consisting of overlapping yellow, red, and blue squares with a black crosshair.

Remedial Objectives

- Risk based; vapour and groundwater flow to aquatic environment

<u>Unit</u>	<u>Compound</u>	<u>Soil</u>	<u>Water</u>
Fill	Benzene:	30 mg/kg	3 mg/L
	Toluene:	100 mg/kg	3 mg/L
	Xylene:	100 mg/kg	-
SILT	-	-	-
SAND	-	-	-

A decorative graphic on the left side of the slide, consisting of overlapping yellow, red, and blue squares with a black crosshair.

Conceptual Remedial Plan

- Groundwater depression / SVE
 - 9 treatment blocks with separate GW depression and SVE wells in grids
 - No apparent need for perimeter barrier
 - Thermal or catalytic oxidation for vapour stream
 - Utilize existing permitted biox water treatment plant; 225 L/min capacity plus holding lagoon

A decorative graphic on the left side of the slide, consisting of a black crosshair. The vertical line of the crosshair passes through a yellow square, and the horizontal line passes through a blue square. There are also some red and white pixelated or blurred areas around the intersection.

Additional Investigations

- 3 major data gaps:
 - Depth, nature, and continuity of silt
 - Groundwater flow/dewatering requirements
 - SVE design parameters

A decorative graphic on the left side of the slide, consisting of a vertical black line, a horizontal black line, and several overlapping squares in yellow, red, and blue.

Additional Investigations

- Depth, nature and continuity of silt layer
 - Drilling and Shelby tube sampling program
 - Grid CPT to accurately define location & nature
- Conclusions:
 - Silt unit locally over-excavated, varied from >1.5 m clayey silt to 0.3 m silty sand; possibly absent in areas




Additional Investigations

- Groundwater flow/dewatering modeling:
 - Three sources of water: rainfall, lateral inflow, vertical upflow through silt
- Conclusions:
 - Could handle up to 3 acres remediation blocks (4 total)
 - Need both perimeter and interior dewatering

A decorative graphic on the left side of the slide, consisting of overlapping yellow, red, and blue squares with a black crosshair.

Additional Investigations


- SVE design parameters
 - SVE pilot test and modeling
- Conclusions:
 - Long period of high vapour concentrations
 - Relatively short asymptotic tails consisting mainly of xylene
 - 180 days or less to clean-up at 10 m x 10 m grid, 35 cfm/well



A decorative graphic consisting of a black crosshair. The vertical line is on the left, and the horizontal line is at the bottom. To the left of the vertical line are three overlapping squares: a yellow one on top, a red one in the middle, and a blue one on the bottom.

Remedial Design

- Low-vacuum dual-phase approach selected
 - Dual purpose wells
 - Maximize dewatering efficiency
 - Minimize mounding & capillary saturation (10 m spacing)
- Perimeter dewatering wells
 - Double row of conventional eductor well points
- Four remediation blocks






Design Parameters SVE System



- 88 SVE wells (stainless/PVC)
- 43" H₂O vacuum
- 35 cfm/3" diam well; 20 cfm/2" diam well
- 10 gpm total groundwater flow (30% of total)
- 2 – 1000 cfm rotary lobe blowers @ 15 hp each

Design Parameters SVE System



A decorative graphic consisting of overlapping yellow, red, and blue squares with a black crosshair.

Design Parameters Eductor System

- 94 dewatering wells
- 0.9 L/min/well; 85 L/min total
- Max depth 5 m below eductor
- Total motive flow 220 L/min @ 50 psi
- 2.4 L/min/eductor
- 2 – 5 hp submersible pumps in recirculation tank

Design Parameters Eductor System



A decorative graphic on the left side of the slide, consisting of overlapping yellow, red, and blue squares with a black crosshair.

Design Parameters Oxidizer

- Convertible catalytic/thermal
- 2000 cfm capacity upgrade potential to 3000 cfm
- 99.9% destruction efficiency in both catalytic and thermal modes necessary to meet local discharge requirements

Design Parameters Oxidizer





Design Parameters

Piping



- Design losses approximately 1" H₂O/100ft
- 0.5% slope in SVE pipe toward KO tank
- Adjustable slurp tube height

Design Parameters Piping





A decorative graphic consisting of a black crosshair. The vertical line is on the left, and the horizontal line is at the bottom. To the left of the vertical line, there are three overlapping squares: a yellow one at the top, a red one in the middle, and a blue one at the bottom.

Operational Issues

- >100 dBA measured 10 m from SVE blower discharge
- Failure of oxidizer plenum and heat exchanger tubes
- Solution:
 - Vibration dampeners installed at blower discharge

Operational Issues



A decorative graphic consisting of overlapping yellow, red, and blue squares with a black crosshair.

Operational Issues

- Water carryover through knockout tank to rotary lobe blowers
- Solution:
 - Install secondary knockout tank

Operational Issues



A decorative graphic consisting of a black crosshair. The vertical line is on the left, and the horizontal line is below the title. There are three overlapping squares: a yellow one at the top left, a red one in the middle left, and a blue one at the bottom left.

Operational Issues

- Greater groundwater recovery rate in SVE wells than anticipated (insufficient vacuum available)
- Solution:
 - Upgrade motors to 40 hp



Operational Issues

- Fouling of wellheads with ferrous iron and benzoic acid
- Solution:
 - Periodic well jetting


A decorative graphic consisting of a black crosshair. The vertical line is on the left, and the horizontal line is below the 'Remediation' part of the title. To the left of the crosshair are three overlapping squares: a yellow one on top, a red one in the middle, and a blue one on the bottom.

Remediation Success

- Estimated 230,000 kg BTX removed in vapour phase (Sept 2003)
- 85% toluene, 6% benzene, 9% m-xylene
- 50,000 m³ groundwater treated through Biox plant
- 15,000 kg BTX removed in water phase

Remediation Success

Cumulative Vapour Phase BTX Extracted



Questions and Answers