Thermal Desorption Remediation In Relation to Landfill Disposal At Isolated Sites in Northern Alberta

ESAA Remediation Technology Conference Banff, Alberta October 21, 2005

ATCO Electric Ltd.

Greg Walker, Michael Henze

Nelson Environmental Remediation Ltd.

Darryl Nelson

Thurber Engineering Ltd.

Brian MacKinnon, Neal Fernuik



Presentation Outline

- ATCO Remediation Project Introduction
- Thermal Desorption (TD) process description
- Quality control and quality assurance
- Steen River TD Project two TD remediated sites
- TD Contracting performance payment / tonne (T)
- Production rates and on-stream utilization
- % cost breakdown/T fuel, labour, capital, peripherals
- Cost comparison TD vs Dig and Dump (DD) in \$2004
- TD advantages mobility, contaminant destruction, groundwater treatment, and winter remediation
- TD limitations salts, metals, fuel and water cost sensitivity and time onsite
- Fox Lake Staged TD Remediation and Aboriginal employment

ATCO Remediation Project

- ATCO identified 103 isolated generating sites
- 77 of these sites are to be remediated and/or reclaimed
- Alberta Environment (AENV) 2001 guidelines
 Alberta Soil & Water Quality Guidelines for
 Hydrocarbons at
 Upstream Oil and Gas
 Facilities
- Remediation criteria depends on site location, zoning and end land use



Site Contamination

- Contamination mainly through the loading, storage and dispensing of diesel fuel
 - Diesel releases offloading diesel, fuel filter, hose, piping and joint failures, and aboveground or underground storage tank releases
 - Petroleum lubricants, polychlorinated biphenyls (PCBs), polycyclic aromatic hydrocarbons (PAHs), glycols, and metals generated limited contamination

TD Operating Steps



Soil preparation at TD

TD Soil Treatment



Thermal desorption - rotary kiln
 Treated soil discharge and quenching

TD Operating Steps



- Contaminant off gas and dust treatment baghouse
- Contaminant destruction and exhaust afterburner/oxidation

Quality Control and Quality Assurance

- TD test burns (200 T stockpiles) determine operating parameters – temperature and residency time
- TD production 1,000 T stockpiles
- Stockpile testing
 - four headspace vapour tests; highest two samples -
 - two PetroFlag immunoassay field tests; highest one –
 - laboratory chemical analysis

Steen River 2004 TD Project

- TD Feasibility Study TD comparable to DD at \$47/T, 150 km & 4,000 T
- TD remediation of 29,000 T of diesel contaminated soil
- Two sites Steen River Microwave and Steen River Community
- 150 km north of High Level, Alberta
- High grade paved highway
- Productivity in fine and coarsegrained soils
- TD winter operations direct, indirect and total project costs
- Compared with similar 2004 DD sites



Steen River Microwave 21,900 T of clay-silt soil



Steen River Microwave TD

- Excavation Volume
- Truck haul
- Soil Volume
- Soil Cost/T
- Average Productivity
- Total Project Cost
- Project Cost

11,100 m³ 560 truck loads - 17 km to TD 21,900 T soil in 45 days \$47/T \$1,029,300 treatment 486 T/day (fine-grained) \$1,572,000 \$141/m3 Wabasca DD 11,110 m³ 490 trucks – 146 km 15,400 T in 29 days \$20/T \$384,000 tipping 530 T/day \$1,540,000 \$139/m³

\$147,000 trucking PHC to TD and backhauling treated soil to SRM

Steen River Community Power Plant 6,500 T sand and gravel



Steen River Community TD Foggy Mountain DD Total Excavation 5,900 m³ in 34 days 5,225 m³ in 35 days 159 trucks – 2 km to TD 260 trucks - 160 km **Truck Haul** TD Soil Processing 6,500 T soil in 12 days* 6,927 T in 29 days* *= Operational days - not including weather delays for Foggy Mountain DD Average Productivity 540 T/day (coarse-grained) 237 T/day TD Soil Processing 47/T = 305,500 $19 \/T = \131,500$ \$844,000 Total Project Cost \$780,000 **Project Cost** \$132/m3 \$152/m³

Steen River Project Total Project Cost (%)

NER TD Soil Processing Cost at 47 \$/T
 NER Peripheral Costs

 site preparation, excavation, trucking, backfill, compaction site reclamation, rentals and water supply

 Other ATCO Costs

 project administration, consultation and chemical analysis
 Total % Project

55% 26%

<u>19%</u> 100%

NER Steen River Project Soil Processing Cost (%)

Soil processing \$47/T

- 20-30% fuel
- 40% labour
- 20% plant and equipment
- 10% peripherals soil handling, tank rentals



TD Variable Costs and Requirements

 Fuel is the largest variable cost factor TD fuels; diesel, natural gas, propane, heating oil and recycled oil cost depend on local cost and availability
 Fuel consumption - soil moisture content and grain size, fuel type and energy yield

 Water Supply – quantity, quality and rate is second most important TD process requirement

TD requires 200 L water/T or ~ 100 m³ water/day

At Steen - water permit for the Hay River, however used onsite dugout

DD versus TD Considerations

Key considerations when comparing TD and DD

- Landfill distance, availability, fees and available backfill
- Available time frame for site remediation
- Trucking costs and availability
- Fuel costs and availability
- Water TD requires ~ 100 m³/day

Road permitting, access, and maintenance costs

TD ADVANTAGES

- TD locate where highway trucks have road access gravel, ice roads and bridges
- TD once present, nearby (satellite) site remediation costs improve, DD economics remain unchanged
- TD less dependent on trucking TD shorter hauls, fewer trucks
- Cost Exposure Trucking invoiced hourly, paid based on tonnage – weather (road maintenance), truck delays increase cost
- Remediate contaminated groundwater using the TD quench system
- TD year-round operation clean, unfrozen fill for winter compaction, DD requires alternate suitable, unfrozen backfill source
- TD less weather-dependent than DD trucking

TD CONSTRAINTS

- Ineffective remediation of salts and metals
- Excavate and truck faster than excavate and TD can process soil
- Fuel TD is more cost-sensitive due to greater fuel consumption relative to DD sites
- Requires 100 m³/day of suitable water

Fox Lake Staged Remediation



- Remediation February 21 March 21 2005 18,000 m³ (46,000 T)
- 1,150 m Ice Bridge 1.5 m thick 105 T rating 40 days to build
- Truck max. speed on ice bridge, loaded or empty 5 km
- 1,100 truckloads 22 km, 24 hrs/day, 2.25 hr cycle time/truck
- Site preparation/complete demolition
- Excavation
- 1,100 trucks hauling PHC soil to TD for processing
- 2,600 trucks hauling free backfill to excavation
 - Sub-total
- TD Soil Processing 46,000 T at 55 \$/T (3 months)
- \$67,000 \$373,000 \$730,000 <u>\$300,000</u> \$1,470,000 \$2,555,000

Fox Lake Aboriginal Content

- Aboriginal content Little Red River Cree Nation
- Little Red River Forestry supplied 40 person camp
- Aboriginal Liaisons Wayne Erasmus and Alex McGillivray facilitated Band Council Resolutions for site access, backfill sources, 24 hour site activities and community traffic controls
- During Excavation Nelson employed 14 aboriginal equipment operators, truck drivers and general labourers
- During TD Nelson employed 8 aboriginal equipment operators, truck drivers and general labourers

Thermal Desorption Remediation In Relation to Landfill Disposal At Isolated Sites in Northern Alberta

ESAA Remediation Technology Conference Banff, Alberta October 21, 2005

ATCO Electric Ltd. Greg Walker, Michael Henze Nelson Environmental Remediation Ltd. Darryl Nelson Thurber Engineering Ltd. Brian MacKinnon, Neal Fernuik