

Integrated Strategy to stimulate application of *in-situ* remediation approaches

TNO | Knowledge for business



Hans van Duijne

RemTech 2007, Banff, Canada

October 24-26, 2007

Geological Survey of The Netherlands


TNO Built Environment and Geosciences

Subsurface and Groundwater

The Netherlands



Contaminated sites in The Netherlands per municipality - 2005



600.000 potentially contaminated sites



Area: 42.000 km²


Population density: 481 persons/km²

Gas Works Facility (1962)






Number of Potentially Contaminated Sites per Municipality 2005



- Total Surface: 41.526 km²
- 600.000 sites are suspected of soil pollution
- 58.000 need remediation
- 12.000 urgent remediation (< 2015)

Soil and Groundwater Remediation: More than just technologies



Brief History



- Legislation
- Inventarisation of the problem
- Remediation
- Soil Contamination perceived as risk

<1980

>1980

Lekkervek 1980

- No soil policy
- No funding
- No awareness



- 1983 Soil Remediation Law
- 1995 Soil Remediation in Soil Protection Law
- 2005 New Policy in Soil Protection Law
- 2007 New Policy in Soil Protection Law

Lack of confidence in-situ remediation technologies

- In-situ techniques not fully matured
- In-situ techniques insufficiently demonstrated in back yard
- No standardized approach to remediate common situations
- Mind set of competent authority/regulators lacks confidence in in-situ techniques:
 - “Outcome uncertain and risks difficult to manage”
 - Insufficient flexibility to deal with risks and uncertainties
 - Processes (authorisations etc.) with soil remediation too complex (many stakeholders, red tape)
 - Lack of knowledge and experience at daily practice level

Why Holland In-situ Program (HIP)?

Growing attention in (sub-)urban brownfields to:

- Provide building space in a densely populated area
- 600.000 contaminated sites, 90% in urban environment
- Ministry of Environment adjusted its policy for the soil remediation plan until 2030
 - Adopting risk based approach: only the “immediate risk” sites to be remediated
 - Risk driven clean-up plan:
 - 15.000 high priority risk sites, in 10 years
 - 60.000 risk carrying sites, in 30 years
 - Shallow contamination needs to be remediated;
 - Targets made flexible (land use, costs and risks)
 - Industrial sector oriented programs
 - From 900 to 2000 sites/yr remediated

Innovation added to full scale projects

- Duration 3 years (2007-2010), 24 in-situ projects,
- 10 contracting firms with financial contribution
- Biological-, physical-, and chemical technologies and combinations
- Development of standardized in-situ technologies for situations with a high occurrence (a high repetition factor, low costs, good market position)
- Process pilots
- Decision support tool - Soilection

Towards standardized reliable and accepted in-situ technologies: the "Holland In Situ Demo" project (HIP).

Site Characteristics		Occurrence (% of total)
Contaminant type (C)	C.1 Chlorinated Hydrocarbons	45
	C.2 Aromatics/Oil/MTBE/Cyanide	45
	C.3 Other	10
Geo-hydrology (G)	G.1 Permeable (sandy)	45
	G.2 Layered, permeable and impermeable layers	45
	G.3 Other	10
Built Environment (B)	B.1 Urban	70
	B.2 Industrial	25
	B.3 Other	5

HIP technical pilots

- In situ bioremediation of a creosote contaminated site by DNAPL extraction and stimulated biodegradation
- Example of a suite of in situ technologies at a dry-cleaning contaminated site in the Netherlands
- Monitoring enhanced anaerobic bioremediation at contaminated sites in the Netherlands; The use of specific monitoring tools


Mega Site Approach –Rotterdam project



More Information on: <http://www.euwelcome.nl/kims/>

In-Situ Remediation Approach

Contaminant **Source** → **Plume** → **Receptor**



Remediation Approach

- Cost-effective technologies
- Split source and plume remediation


Figure 4.2. Classical contaminant conceptual model.

M. Rivett, J. Drewes, M. Barrett, J. Chilton, S. Appleyard, H. Dieter, D. Wauchope and J. Fastner

Chapter 4 – p. 5

Integrated Management Strategy

- 1 Identifying Risks (Site Characterization + Risk Assessment)
- 2 Determining the degree of contamination removal required
- 3 Calculation of necessary investments
- 4 Selection of most cost effective scenario



Possible Significant Effects on GWQ; time frame, 2020-2060. Contribution NA??


Significant Effects on GWQ; time frame, 2005-2040

No significant Effects on SWQ




3rd plane of compliance


Regional Groundwater flow




2030: Chance of exceeding intervention value at 3rd Plane of Compliance



Autonomous scenario (impact on POC 3)



Scenarios for effect of risk management measures (e.g. source removal, NA, Isolation)



Soil and Groundwater Remediation: More than just technologies

