

SUSTAINABLE LANDFILL BIOCELL

AN INNOVATIVE TECHNOLOGY TO BIOSTABILIZE
ORGANIC FRACTION OF MUNICIPAL SOLID WASTE

RemTech 2010
October 22nd, 2010

Don Davies
Stantec Consulting Ltd.

Corey Colbran, P.Eng.
The City of Calgary



OUTLINE

- Organic Fraction of Municipal Solid Waste (MSW) Stream.
- Waste Biostabilization in a Conventional Landfill.
- Conventional vs. Biocell Landfills.
- Biocell Landfills – Introduction.
- Case Study – City of Calgary Sustainable Landfill Biocell.
- Operation / Monitoring.
- Future.

This project received a 2006 Consulting Engineers of Alberta Showcase Award of Excellence.

ORGANIC FRACTION OF MUNICIPAL SOLID WASTE STREAM

- Approximately 70% of waste currently landfilled is organic.
 - ↳ Yard waste (25%), Food waste (20%), Paper (25%).
- Up to 75% of MSW generated in the region is disposed to landfills.
- Decomposition of organic fraction of MSW in a landfill generates landfill gas (mainly CH_4 and CO_2) and leachate.

WASTE BIOSTABILIZATION IN A CONVENTIONAL LANDFILL




Figure 1: Phases of Decomposition of Organic Fraction in a Landfill

CONVENTIONAL VS. BIOCELL LANDFILLS

- Conventional landfills - “dry tomb” philosophy.
- Could take 100 or more years for complete biostabilization in drier climates.
- Current regulations include long-term post closure monitoring requirements.
- Biocell landfills – decomposition occurs in a shorter period of time.
- Biocell landfills are designed and operated to minimize short-term risks associated with leachate and LFG.


BIOCELL LANDFILLS – AN INTRODUCTION

- Designed/operated to ensure favorable conditions are created for rapid biodegradation of organic waste.
 - ↳ Landfills as “process vessels”.
- The most significant factor affecting waste biodegradation is moisture.
- Leachate recirculation.
- Operated near the field capacity of the waste.
- Phases are: anaerobic, aerobic, and recovery of air space.
- Opportunity to process various organic wastes for beneficial end use.

WHY BIOCELL LANDFILLS?

- Potential exists for air space recovery.
- Lower costs associated with leachate treatment. No need for treatment at wastewater treatment plants or purpose-built facilities.
- LFG recovery and treatment.
- Lower long-term risks (e.g. leachate and LFG).
- Lower post closure costs (e.g. leachate disposal and LFG).
- Potential for resource recovery and recycling.
- Potential for greenhouse gas (GHG) emission reduction.
- Potential to generate energy.

ANAEROBIC PHASE OF BIOCELL LANDFILL



AEROBIC PHASE OF BIOCELL LANDFILL

Aerobic Bioreactor




Leachate / Liquids Addition
Air Injection

CASE STUDY: CITY OF CALGARY SUSTAINABLE LANDFILL BIOCELL

- Genesis.
- Pilot facility for a full-scale biocell landfill.
- Potential sustainable waste management option for The City of Calgary.
- Contains 55,000 tonnes of residential organic waste.
- Incorporates the advantages of anaerobic and aerobic processes.
- Unique project – developed the term Landfill Biocell (LBC).
- Research – University of Calgary was involved.

SUSTAINABLE LANDFILL BIOCELL CONCEPT



LBC DESIGN

- Components of the LBC:
 - ↳ Groundwater Control System (in-gradient).
 - ↳ AENV Compliance (permeability).
 - ↳ Composite Liner System.
 - ↳ Leachate Collection and Storage System.
 - ↳ Liquid Injection System.
 - ↳ Common LFG Collection / Air Injection System.
 - ↳ Bio-cap Intermediate Covers.
 - ↳ Final Cover.

DESIGN CHALLENGES

- Higher initial infrastructure capital costs versus conventional landfills.
- Supplementary moisture sources may be required.
- Subsidence (i.e. Instrumentation Cluster Wells).

LBC CONSTRUCTION



LBC CONSTRUCTION CONTINUED



LBC FILLING



- Bag breaking.
- Density of waste.
- Subsidence.
- Intermediate bio-cap.

LBC CONTROL SYSTEM

- Main performance parameters for process monitoring, control, and evaluation – temperature, gas concentration, and moisture content.
- Liquid injection and gas collection are controlled.

LBC CONTROL DURING CONSTRUCTION



BIOCELL OPERATIONS

- DBM was based on source separated organics but the biocell was filled with residential MSW.
 - ℒ Source separated organics was not considered feasible at the time.
 - ℒ Filling operations were taking a long time so residential trucks were diverted to the biocell from both Shepard and East Calgary Landfills.
- Positives:
 - ℒ Very good gas production and quality.

Year	LFG Volume (m ³)	Methane Volume (m ³)	% Methane
2007	548,015	290,448	53.0 %
2008	555,288	280,420	50.5 %
2009	445,002	234,024	52.6 %

- ℒ LFG generated from the Biocell represents about 30 - 35% of the total volume recovered at the Shepard landfill site. Plays an important role in the generation of electricity at the site.

BIOCELL OPERATIONS

- Issues:

- ↳ Failure of the facility's automated controls and instrumentation caused by lightning strike. System could function safely manually, but automated control and data collection systems were affected.
- ↳ Landfill Gas Collection Manifolds.
 - Issues with freezing during cold weather.
 - Manifolds were designed to come to ground level concrete pad prior to joining LFG collection network. Condensation froze and eventually blinded the manifolds for LFG for the first winter.
 - First covered with soil, then covered with small structures with explosion-proof heating.

BIOCELL OPERATIONS

- LFG seepage at seam where bottom liner meets top liner (GSM). Capped with clay to minimize emissions.
- Temperature probes faulty. 49 installed, 11 functioning.
- Some areas of the biocell appear to have unsaturated portions where gas production is low. Potentially crushed leachate return piping during construction.
- Settlement gauges which went out of range during filling operations.

LOOKING TO THE FUTURE

- Repairs to be made to return biocell to full automation.
- Must then look to the aerobic phase of biocell operation.
 - ↳ Once aerobic phase is completed and cell excavated, we will get a clear picture of how the waste has decomposed, what is required operationally (screening, etc.), and how the materials of construction fared.
- Next step will be to reuse the reclaimed airspace and look towards building another, or a series of, biocells.

CONCLUSION

- Diversion strategies will need to acknowledge that, even with aggressive diversion programs, some percent of organic waste will remain in the MSW waste stream.
- Biocells reduce long term risks associated with conventional landfills.
- Biocells treat waste as a resource.
- Biocells could provide a sustainable method of managing organic fraction of MSW.
- Biocells could provide a sustainable method of managing other organic wastes as a resource.

QUESTIONS?

