

The New Science Centre 2011 Project

Case Study: Design Optimization of an Active Sub Slab Depressurization System to Mitigate Vapour Intrusion of Methane Gas from Former City of Calgary Landfill

Presented by: Sean K. Ezekiel, Environmental Engineer
AMEC Environment & Infrastructure



- Proposed Development
- Project Background
- Environmental Management Controls
- Vapour Intrusion
- Methane Properties
- Methane Mitigation Controls
- Secondary Methane Mitigation Controls
- Results
- Performance Monitoring
- LEED in Brownfield development

Proposed Development – New Science Centre



- 153 000 ft² new science centre to replace former science centre that was in operation for 44 years
- Built on a structural slab foundation
- Three story complex with attached dome theatre
- First new state-of-the-art science centre in Canada in the 21st Century
- Municipal, Provincial and National hub for innovation
- Opening October 29th, 2011



Project Background – Site Description



Project Background – Historical Environmental Investigations



AMEC involved since the early 1990s:

- Bird and wildlife surveys
- Surface water quality assessment
- Extensive drilling/sampling to assess soil and GW conditions
- Human Health and Ecological Risk Assessment
- Preparation of a RAP to use site as a Urban Park
- Engineering report in support of application for variance of landfill setback
- Environmental Management Plan (EMP) in support of DP



Project Background – Key Environmental Concerns



Environmental Management Controls




- Removal of waste piles prior to construction
- Characterization, segregation and offsite removal of waste debris encountered during construction
- Importation of fill to raise surface elevation ~ 2m to mitigate impacts of being located in a flood fringe
- Collection of surface water to avoid direct runoff into the adjacent Nose Creek
- **Implementation of mitigation measures to address VI potential into site building from underlying C&D wastes and adjacent MSW**



What is Vapour Intrusion?


- Soil gas migration from subsurface to overlying and/or adjacent buildings
- Common Sources
 - Methane
 - Radon
 - VOC's
- Transport
- Preferential Pathways



Provided by ITRC, January 2007

Methane Properties

- CH_4
- Simplest hydrocarbon (alkane)
- Gas at room temperature
- Less dense (lighter) than air
- Forms explosive mixtures with air (5 – 15% Gas)
- Colourless
- Odourless
- Relatively insoluble in water
- Simple asphyxiant



Methane Mitigation Controls – Design Objective



***To reduce the potential for methane gas to accumulate
to harmful levels inside site facilities***

Methane Mitigation Controls – Design Challenges



- Structural Slab
 - Sub slab settlement
- Building size/configuration
- Shallow groundwater
 - moisture
- Visibility
 - interior aesthetics
 - exterior - Hwy 2/C-train route, urban park, residential
- Acoustics
 - adjacent residential neighborhood
 - Internal vibrations/noise levels
- Energy efficiency
- Minimal maintenance
 - completely automated



Methane Mitigation Controls – Design Selection



- Primary Mitigation Technology Selected:
 - Active sub slab depressurization (SSD) selected
- Optimization features:
 - Variable Frequency Drive
 - Inline combustible gas sensor
 - Acoustical Isolation
 - Contingency moisture knockout
- Secondary Mitigation Controls
 - Inbuilding monitoring system
 - Utility blocks/vents



Methane Mitigation Controls – SSD




- Key System Components
 - Powered extraction unit
 - General synthetic barriers not required
 - Permeable layer beneath floor slab (e.g. gravel)
 - Perforated piping network completed with risers for venting of soil gas
 - Hangers to suspend collection piping


- Design parameters
 - Flow = 3000 CFM
 - Vacuum = 50 in. H₂O
 - Sub slab vacuum range = 0.01 to 0.1 In.H₂O

- Equivalent pipe length method used to size piping


SSD – Sub Slab Piping Layout




SSD – Perforated/Solid Collection Piping



SSD – Header System



SSD – Extraction Fan



SSD - Variable Frequency Drive/Inline Combustible Gas Sensor



Extraction fan speed is controlled by a VFD and inline combustible gas sensor


- Low Speed = 50% capacity or 1500 cfm
- High Speed = 100% capacity or 3000 cfm

Fan Sequence of Operation

- If inline methane concentrations remain below 15% LEL fan runs continuously at Low Speed.
- If inline methane concentrations exceed the 15% LEL set point, fan is increased to High Speed; fan remains at high speed until concentrations fall back below the set point.



SSD - Exhaust Acoustical Isolation




Secondary Mitigation Controls - Inbuilding Monitoring System




Two Stage In-building Alarm System tied to BMS


- Alarm # 1 > 5% LEL (2 500 PPM):
 - activation of HVAC system
 - automated notification to property manager
- Alarm # 2 > 25% LEL (12 500ppm):
 - evacuation via activation of fire alarm system
 - activation of blue strobes located at employee entrance
 - METHANE specific signal sent to Fire Department message
 - automated notification to property manager
- Sensor locations based on:
 - manufacturers area of coverage
 - building configuration and confined spaces




Secondary Mitigation Controls - Inbuilding Monitoring System



Secondary Mitigation Controls – Utility Blocks/Vents




Secondary Mitigation Controls – Utility Blocks/Vents



(A) PLAN – UTILITY LINE VENT AND UTILITY BLOCK TYPICAL
SCALE N.T.S.


Results: Design vs. Actual Flow Rates



Results: Sub Slab Pressure 30 Hz




Pressure Field @ 30 Hz




Results: Sub Slab Pressure 60 Hz



Pressure Field @ 60 Hz



Cost Comparison



Post Construction SSD System Refinement

- Refinement efforts undertaken to allow for modification to pressure fields and fan speed/size
- Refinement based on attaining as even as possible vacuum beneath floor slab via:
 - Adjustment of fan speed and types
 - Adjustment of valves at header to control flow
- Sub-slab Vacuum monitored through access ports connected to low vacuum sensitivity gauges



LEED in Brownfield Development



- New Science Centre applicant for LEED certification
- Sustainable Site, Credit 3 – Redevelopment of Contaminated Sites

Questions?



Sean K. Ezekiel, Environmental Engineer

AMEC Environment & Infrastructure
140 Quarry Park Blvd SE
Calgary, AB T2C 3G3
Phone: (403) 248-4331
Sean.Ezekiel@amec.com