

RemTech 2015

MATCON

Jet Grouting – an alternate for environmental cut-off

Stephen Custéau P. Eng., Matcon Environmental
Paolo Gazzarrini P. Eng., Sea to Sky Geotech


Summary

MATCON

- History of Jet Grouting
- How the technology is working
- Applications
- Case Histories for environmental applications
 - Recochem Port Coquitlam
 - New Westminster Pier
 - John Hart Dam (cut off)

History

MATCON



-Japan (CCP) 70's

- Europe late 70's

- NA – middle 80's


Standards

MATCON

**GEO-INSTITUTE OF ASCE
GROUTING COMMITTEE
JET GROUTING TASK FORCE**

JET GROUTING GUIDELINE

June 2009



<http://content.geoinstitute.org/files/pdf/G-I-ASCE.JetGrouting.Guideline-final.doc>


Page 1 of 30

Copyright © American Society of Civil Engineers


How is working

MATCON


STEP 1 : DRILLING




STEP 2 START JETTING WITH W/C GROUT MIX FROM THE BOTTOM



STEP 3: PULL UP THE ROTATING JET



RESULT: ROUND COLUMN CONSISTING OF WATER/CEMENT MIX AND INSITU SOIL



How is working

MATCON



SEA TO SKY
Geotech Inc.

MATCON
CANADA
MESL Group of Companies

Result

MATCON



SEA TO SKY
Geotech Inc.

MATCON CANADA
MESL Group of Companies

Result

MATCON




SEA TO SKY
Geotech Inc.

MATCON
CANADA
MESL Group of Companies

Geometry

MATCON



Environmental

MATCON





Fig. 9 - Grout curtain used to isolate waste from flowing groundwater. (from USEPA, 1978)

Typical Site Installation

MATCON



JG parameters

MATCON

- Pressure p (MPa) - Grout Mix and/or Air water in case of D&T
- Flow Q (m^3/hr) - Grout Mix and/or Air water in case of D&T
- Diameter d_n (mm) and number (N) of nozzles. These give the total area of the nozzle A_n (mm^2)
- Velocity of withdraw of the rods or Treatment Velocity v_t (m/hrs or cm/sec)
- Specific Volume of Fluid jet-grouted V (m^3/m) and consequently volume of cement (Kg/m)
- Rotation speed of the rods v_r (rpm)
- Composition of grout mix in terms of W/C ratio.

Range of Results

MATCON

Type of Soil	Diameter (m)			UCS (Mpa)	E (Mpa)
	Single fluid	Double Fluid	Triple Fluid		
Gravel	0.6-1.2	1.0-1.6	2.0-3.0	10-30	2,500-15,000
Sandy Gravel	0.5-1.0	0.9-1.8	1.5-3.0	8-20	2,500-10,000
Silty Clay	0.5-1.0	0.8-1.5	1.2-2.8	5-15	2,500-7,500
Clayly Silt	0.4-0.6	0.7-1.0	1.0-1.5	2-8	1,000-5,000
Clay	0.4-0.8	0.6-1.2	0.8-1.2	1-6	500-5,000

Permeability= 10^{-6} to 10^{-8} m/s
Depending on soil conditions and grout
Mix (with or w/o bentonite).

Field Test

MATCON



SEA TO SKY
Geotech Inc.

MATCON
CANADA
MESL Group of Companies

QC at the Grout Plant

MATCON




QC- Monitoring and recording jetting

MATCON



MATCON
CANADA
MESL Group of Companies


QC- Monitoring and recording jetting



QC- Monitoring and recording jetting

MATCON

MATCON Engineering & Services Ltd.		John Hart Dam JETGROUTING (Contract 200)		
Date : 8/30/2011	Rig : HH008	Drilling volume : 0.663 m ³	Drill Depth : 0.00-17.41 m	
Begin : 8:28:48 AM	Drilling duration : 00:07:45	Grout volume : 28.103 m ³	Jet Depth : 1.20-17.41 m	
End : 11:33:24 AM	JET duration : 01:53:46	Volume by meter : 1784 l/m	JET Length : 18.21 m	
1/10 Column JHDT18			EX.JTC 6.68.98/IC3/JTC879EN	




Verticality

MATCON




Verticality

MATCON



Verticality

MATCON



Verification

MATCON

- Coring
- Permeability tests (direct-indirect)
- Cross/holes, tomography
- Calipers
- Load test in case of piles

Case History in BC

MATCON

- 19) Lynn Sewage Pumping Station, North Vancouver. Shoring and cutoff wall. 20) 21) 22) 23)
- 18) Edgemont Village, North Vancouver.
- 17) Trapp & Holbrook – 660 Columbia Street, New Westminster.
- 16) The Mandarin, Richmond - Jet Grouting for shoring, underpinning and cutoff wall.
- 15) Multi-Use Facility centre - City of New Westminster - Shoring and cutoff wall.
- 14) Zeballos (Vancouver Island) -Design and execution of a 75 diameters p cut off using Jet Grouting technology.
- 13) John Hart Dam – Flexible Jet Grouting cutoff.
- 12) Science World- Soil improvement against seismic liquefaction. Jet Grouting/ Compaction Grouting.
- 11) New Westminster Pier – Impervious environmental cutoff wall.
- 10) Iona treatment plant (GVRD- Vancouver) . Shaft for manhole sewer excavation. Siphon 1, 2 and 3, in 3 years.
- 9) BC Hydro Walter Substation North Vancouver- Jet grouting for concrete slab soil improvement against liquefaction.
- 8) Port Coquitlam. Cutoff for contaminated soils.
- 7) Pemberton Ave.- North Vancouver- Cutoff for contaminated soils
- 6) Olympic Village – False Creek – Vancouver- Jet Grouted cut off and shoring wall.
- 5) Richmond – Paloma Parkade- Jet-Grouted piles.
- 4) Clarkson & Sixth- New Westminster - Jet Grouting for soil improvement (building foundation) in proximity of Sky train tunnel for settlement control.
- 3) 102 st./King George Highway –Surrey - INFINITY- Shoring.
- 2) Esplanade & St. George North Vancouver - Shaft for Sewer installation.
- 1) Esplanade & Lonsdale North Vancouver - Underpinning of CN tunnel in North Vancouver BC for shoring.

Major JG works

MATCON

- Shoring/CutOff/Underpinning:
 - North Vancouver - Parcel 5
 - Richmond – The Mandarin
- Shoring/CutOff:
 - False Creek- Olympic Village
 - New Westminster- Multiuse Facility Centre
- CutOff (environmental and not)
 - Recochem Port Coquitlam
 - New Westminster Pier
 - John Hart Dam
 - Zeballos Lake
- Soil Improvement for Settlement Control
 - New Westminster- Clarkson & Sixth
- Piling
 - Richmond – Paloma Parkade
- Shafts
 - North Vancouver- Esplanade & St. George
 - IONA Treatment Plant (3 phases)

Recochem Port Coquitlam




SEA TO SKY
Geotech Inc.

MATCON
CANADA
MESL Group of Companies


Port Coquitlam

MATCON






Port Coquitlam

MATCON



Port Coquitlam

MATCON



Port Coquitlam

MATCON



New Westminster Pier

MATCON



Location

MATCON



SEA TO SKY
Geotech Inc.

MATCON
CANADA
MESL Group of Companies

Location

MATCON

AERIAL PERSPECTIVE OVER LYTTON SQUARE
AND FESTIVAL LAWN



The Problem

MATCON

Solvent Plume Area

AB II WESTCOAST NEWS

BREAKING NEWS: YANCOUVEREX.COM | THURSDAY, NOVEMBER 11, 2010

NEW WESTMINSTER

Toxic soil fouls plan for riverfront park

City and environment ministry look for ways to clean up contaminants 10-15 metres deep at Pier Park site

BY THERESA McHANUS

A small portion of the New Westminster Pier Park site is home to a toxic blob of unknown origin.

A Nov. 8 report to New Westminster council states that remediation of contaminated soils at the park has been completed, but recent groundwater testing in the area around Fourth Street has identified a higher concentration of contaminants than was previously known. The contaminant, called tetrachloroethylene, is a common dry-cleaning chemical, which has been found at depths of 10 to 15 metres.

According to the report, the highest concentrations are located a short distance north of the park boundary, within the railway corridor.

"The contamination we found in the area around Fourth Street is a high risk," said Jim Lowrie, the city's director of engineering services. "It's a high-chlorinated solvent."

Lowrie said there are a few options available to address the contaminants because they are so far underground. He said they could be excavated, but that may not be the best option. "We can contain it and pump and treat it," he said. "If it's not mobile, we can leave it."

"The concern is the potential to migrate toward the river," Lowrie said. "The highest concentration is just off-site in the railway corridor. We are doing additional testing."

The Ministry of Environment has prioritized this site "because it's close to the river with political sensitivities around it," said Doug Walton, the manager of the ministry's risk assessment and remediation department. But, he added, tetrachloroethylene is "nothing unusual for us."

Lowrie said the toxic "blob" is about 750 square metres, which is about five per cent of the park property.

A previous laundry facility in the area has been ruled out as the source of the contaminants, but the source has yet to be identified.

"As part of the remediation process, a human health and ecological risk assessment study will be undertaken to assess the degree of exposure to humans and environment in order that appropriate mitigation measures may be implemented," said the report to council.

"Additional groundwater sampling is currently underway to determine if the contaminants are mobile, and to identify the potential source of the contamination."



JOE BONNAR/REDFERNS/CONTRIBUTED
The City of New Westminster is planning a waterfront park for a 3.2-hectare site along Front Street the city purchased last year.

New Westminster resident Christopher Bell has raised concerns about contamination since the city purchased the 3.2-hectare riverfront site last year.

Last week, he met with representatives of the Ministry of Environment and the city for two hours to discuss the park site. "We are not even finished the testing," he said. "They haven't figured out the nature of the problem."

Bell said the area is now considered a high-risk area, rather than a low-risk area, as had been previously thought.

"We bought this real mess for \$18 million without knowing the true toxic nature of this blob," he said.



MAP: CITY OF NEW WESTMINSTER


THE NEW WESTMINSTER RECORD
#10 a/w by Kim Pemberton

MATCON
CANADA
MESL Group of Companies

The Problem


MATCON

Solvent Plume Area



The Options

MATCON



The Site

MATCON



SEA TO SKY
Geotech Inc.

MATCON CANADA
MESL Group of Companies

The Site

MATCON



The Site

MATCON




Verticality Control

MATCON




Mapping The JG

MATCON



John Hart Dam

MATCON




Location

MATCON



Backup Seepage Control


MATCON



Investigation and seepage analysis revealed
that the seepage cut-off wall at the left
abutment of the North Earthfill Dam could be
damaged during a seismic event.

The Challenges

MATCON



- Avoid hydro-fracturing/hydro-jacking and consequent damage of the dam
- Avoid reservoir contamination with JG reflow

ECI Process

MATCON


Early Contractor Involvement (ECI)

Jan –Jun 2011




Target: Study and discussion of procedures/
methodologies to avoid hydro-fracturing
of the dam embankment, to be verified in a
field test.

Soil Conditions



Field Test

MATCON



Field Test

MATCON



SEA TO SKY
Geotech Inc.

MATCON
CANADA
MESL Group of Companies

Drilling Procedures

MATCON




Pre-drilling and
PVC installation



Verticality Measurement

MATCON



Field Test Results

MATCON



SEA TO SKY
Geotech Inc.

MATCON
CANADA
MESL Group of Companies

Field Test Results

MATCON



SEA TO SKY
Geotech Inc.

MATCON
CANADA
MESL Group of Companies

Production Works

MATCON




SEA TO SKY
Geotech Inc.

MATCON
CANADA
MESL Group of Companies

Very Congested Site!

MATCON



Spoil/Reflow Management

MATCON



SEA TO SKY
Geotech Inc.

MATCON
CANADA
MESL Group of Companies

Spoil/Reflow Management

MATCON



SEA TO SKY
Geotech Inc.

MATCON
CANADA
MESL Group of Companies

Spoil/Reflow Management



Spoil/Reflow Measurement

MATCON




SEA TO SKY
Geotech Inc.

MATCON
CANADA
MESL Group of Companies

Real Time Control

MATCON




SEA TO SKY
Geotech Inc.

MATCON
CANADA
MESL Group of Companies

Real Time Control

MATCON



SEA TO SKY
Geotech Inc.

MATCON
CANADA
MESL Group of Companies

QA/QC

MATCON



SEA TO SKY
Geotech Inc.

MATCON
CANADA
MESL Group of Companies


Coring

MATCON



SEA TO SKY
Geotech Inc.

MATCON
CANADA
MESL Group of Companies



Results

MATCON



SEA TO SKY
Geotech Inc.

MATCON
CANADA
MESL Group of Companies

Top of the Wall

MATCON



SEA TO SKY
Geotech Inc.

MATCON
CANADA
MESL Group of Companies

RemTech 2015

MATCON



Questions?

SEA TO SKY
Geotech Inc.

MATCON
CANADA
MESL Group of Companies